Harvest the Sunshine

465W

JA SOLAR

JAM54D41 LR

Black Modules
n-type Double Glass Monofacial Modules

Premium Cells

n-Bycium+ 16BB

MBB Half-Cell Technology


26%

Up To

Cell Conversion Efficiency

Premium Modules

- Higher power generation better LCOE
- n-type with very Lower LID
- Better Temperature Coefficient
- Better low irradiance response



1% 1st-year Degradation


0.4% Annual Degradation Over 30 years

25 25-year product warranty

30 30-year linear power output warranty

Comprehensive Certificates


- IEC 61215, IEC 61730
- ISO 9001: 2015 Quality management systems
- ISO 14001: 2015 Environmental management systems
- ISO 45001: 2018 Occupational health and safety management systems
- IEC 62941: 2019 Terrestrial photovoltaic (PV) modules - Quality system for PV module manufacturing



DEEP BLUE 4.0 Pro

JAM54D41 LR n-type Double Glass Monofacial Modules

DEEP BLUE 4.0 Pro



MECHANICAL PARAMETERS

Cell	Mono
Weight	22kg
Dimensions	1762±2mm×1134±2mm×30±1mm
Cable Cross Section Size	4mm²(IEC), 12 AWG(UL)
No. of cells	108(6×18)
Junction Box	IP68, 3diodes
Connector	QC 4.10-351/ MC4-EVO2A
Cable Length (Including Connector)	Portrait: 400mm(+) /200mm(-) Landscape: 1200mm(+)/1200mm(-)
Front Glass/Back Glass	1.6mm/1.6mm
Packaging Configuration	36pcs/Pallet, 936pcs/40HQ Container


Remark: customized frame color and cable length available upon request

ELECTRICAL PARAMETERS AT STC

TYPE	JAM54D41 -440/LR	JAM54D41 -445/LR	JAM54D41 -450/LR	JAM54D41 -455/LR	JAM54D41 -460/LR	JAM54D41 -465/LR
Rated Maximum Power(Pmax) [W]	440	445	450	455	460	465
Open Circuit Voltage (Voc) [V]	38.90	39.10	40.30	40.50	40.60	40.70
Maximum Power Voltage(Vmp) [V]	32.47	32.65	32.99	33.33	33.68	34.02
Short Circuit Current(Isc) [A]	14.31	14.40	14.41	14.42	14.43	14.44
Maximum Power Current(Imp) [A]	13.55	13.63	13.64	13.65	13.66	13.67
Module Efficiency [%]	22.0	22.3	22.5	22.8	23.0	23.3
Power Tolerance	0~+3%					
Temperature Coefficient of Isc(α_Isc)	+0.045%/°C					
Temperature Coefficient of Voc (β_Voc)	-0.250%/°C					
Temperature Coefficient of Pmax(γ_Pmp)	-0.290%/°C					
STC	Irradiance 1000W/m², cell temperature 25°C, AM1.5G					

Remark: Electrical data in this catalog do not refer to a single module and they are not part of the offer.
They only serve for comparison among different module types.

CHARACTERISTICS



ELECTRICAL PARAMETERS AT NOCT

TYPE	JAM54D41 -440/LR	JAM54D41 -445/LR	JAM54D41 -450/LR	JAM54D41 -455/LR	JAM54D41 -460/LR	JAM54D41 -465/LR
Rated Max Power(Pmax) [W]	333	337	341	344	348	352
Open Circuit Voltage(Voc) [V]	36.81	37.00	38.14	38.33	38.42	38.51
Max Power Voltage(Vmp) [V]	30.73	30.89	31.22	31.54	31.86	32.19
Short Circuit Current(Isc) [A]	11.45	11.52	11.53	11.54	11.55	11.56
Max Power Current(Imp) [A]	10.84	10.90	10.91	10.92	10.93	10.94
NOCT	Irradiance 800W/m², ambient temperature 20°C, wind speed 1m/s, AM1.5G					

OPERATING CONDITIONS

Maximum System Voltage	1500V DC
Operating Temperature	-40°C~+85°C
Maximum Series Fuse Rating	25A
Maximum Static Load, Front	5400Pa(112 lb/ft²)
Maximum Static Load, Back	2400Pa(50 lb/ft²)
NOCT	45±2°C
Safety Class	Class II
Fire Performance	UL Type 38/Class C

JA SOLAR

Headquarters No. 8 Building, Nuode Center, No.1 Courtyard, East Auto Museum Road, Fengtai District, Beijing
Tel: +86 10 6361 1888 Fax: +86 10 6361 1999
E-mail: sales@jasolar.com marketing@jasolar.com www.jasolar.com

Specifications subject to technical changes and tests.
JA Solar reserves the right of final interpretation.

Version No. : Global-EN-20250715C